



PRODUCT NAME

VENTILATED GEAR LOCKER

JUST LOCK IT.

modern-lockers.com

W_E_L_C ТО IIIIIII (RSC **Modern Street** Based in Riyadh and Khobar, KSA, we have been the top e-store for restaurant and café supplies in the Middle East since 2004.

Why Choose Us?



Extensive Inventory



Fast Shipping



Competitive Pricing



Quality Products

Shop Anytime, Anywhere

We are just a few clicks away!

Our platform is accessible 24/7 from any device for seamless shopping.

Dedicated to Your Needs

Your convenience is our priority!

Enjoy rapid shipping, low prices, and excellent customer support with Modern Street EST.

Let's Lead Industry

Modern Street ES is more than a retailer; we are pioneers in the industry!

Trust us to be your go-to source for all restaurant and café supplies in the Middle East.

VENTILATED GEAR LOCKER

Model No: MSG124246

Standard Accessories



Prong Wall Hook



Name/Number Card holder for Lockers



Steel Recessed Cup for Lockers



Barrel Hinge

Dimensions

| Width | Depth | Height |
|-------|-------|--------|
| 18 in | 22 in | 72 in |
| 18 in | 22 in | 72 in |
| 24 in | 22 in | 72 in |
| 24 in | 22 in | 72 in |





Ventilated Gear Locker

Color Options











X4 Verdant Green

X3 Blue Streak 77 Stone Gray 78 Sand

KK Vulcan Black





Standard Accessories



Prong Wall Hook



Steel Recessed Cup (Option 1)



Barrel Hinge



Card Holder

Optional Accessories



Prong Ceiling Hook



Coat Rod



Number Plate



Key Padlock



Combination Padlock



Built-In Lock



Combination Lock With Key



Integrated Lock with Key



Cam Lock



Steel Recessed Cup (Option 2)

NOTE: The optional accessories option states that these items will add an additional price if selected.



Material

Specification

Material

All major steel parts shall be of mild cold rolled commercial quality steel.

Material

Shall be 14 gauge, channel shaped on both the lock and hinge side, with angle formations across the top and bottom. Locker doors shall have a 16 gauge full height reinforcement channel.

Hinges

Shall be barrel (hidden) hinges riveted to both door and frame.

Number Plates

Each locker shall have a polished aluminum number plate riveted to door frame with black numerals 3/8" high.

Finish

All material shall be power washed and phosphate treated for maximum finish color adhesion. All components shall be finished with a hybrid epoxy/polyester powder, electrostatically applied to ensure uniform thickness and baked to cure.

Handles

Shall be one-piece 20 gauge deep drawn stainless steel cup designed to accommodate locks.

Color

Locker color shall be selected from the RAL COLOR CHART.

Construction

All lockers shall be built on a unit principle with common intermediate uprights separating units.

Body

Bottoms shall be 16 gauge. Tops, sides, backs, and shelves shall be 24 gauge.

Latching

Lockers shall have an anti-pry feature secured to the frame. The frame hook shall have a padlock hasp protruding through the recessed handle.

Assembly

Factory-assembled lockers shall be welded.

Door Frames

Shall be 16 gauge formed in a channel shape. Vertical members shall have additional flange to provide a continuous door strike. Cross frame members shall also be 16 gauge channel shaped.

InteriorEquipment

Lockers shall be equipped with a shelf. If under 18" deep, locker shall have three wall hooks and ceiling hook. Lockers 18" deep or more shall have a coat rod instead of a ceiling hook. Lockers 15" wide and wider shall have four wall hooks and one ceiling hook.



Premier Colors

Our preparation and finishing procedures deliver a superior powder coat surface, highly resistant to chipping, cracking, and corrosion, to create a lasting impression for your locker installation. All color chips are reproductions and approximate the actual color as closely as possible. Additional charges apply for custom orders.







Location

Factory No.04, Jabal Al-Zahmi, Bader Area, Imam Muslim Road, Shifha IND, Riyadh, Saudia Arabia

Info@modernstreetes.com sale@modernstreetes.com

Call Us +966 541022221

modern-lockers.com